

20

TranzX
inspiring your ride

TranzX
inspiring your ride

No. 80, Nan Dee Lane, Shan Hsi Village,
Shou Shui Hsiang, 504 Chang Hua Hsien,
Taiwan R.O.C.

T:+886-4-7681756
F:+886-4-7680575

www.tranzx.com

17

JD HISTORY

JD extended global expansion with new European office in Germany – JD Europe Components GmbH. **2008**

JD launched TranzX Power Support Technology at the 20th Taipei International Cycle Show. To set up the Innovative Tech-application & Development Center in Taichung, Taiwan **2007**

JD opened Melton Industrial Co., Ltd. in Dongguan, China - to further expand manufacturing capacity. **2003**

JD introduced JD Bug brand for trendy mobility and youth products. **2001**

JD was awarded Taiwan's prestigious Rising Star Award for outstanding business performance and making a significant contribution to Taiwan's national economy. **1999**

JD commences research and development of environmental-friendly electric mobility systems. **1997**

JD invested in China, beginning construction of JD Metal Industry Co., Ltd. in Shenzhen, China. **1993**

JD launched TranzX brand for bicycle components and successfully markets brand globally. **1992**

Gino Tsai and Tina Lin established JD Components Co., Ltd. as a manufacturer of aluminum bicycle components. **1986**

CONTENTS

02 DROPPER POST

08 ANTISHOCK STEM & SEAT POST

12 STEM

28 HANDLEBAR

36 TRI BARS

39 SEAT POST

50 SEAT CLAMP

58 QUICK RELEASE

62 ISF FORK

64 BAR ENDS

68 HOME TRAINERS

DROPPER POST

Our adjustable seat post equips air pressure actuation – freely and easily adapting your seat position according to the terrain you meet
The MICRO adjustment offers quick and easy seat positioning, with reliable and robust technology – virtually No Play!



JD - YSP06

NEW

ISO MTB

Wireless 2.4 GHz version to allow absolute ease in assembly without cable routing hassle
A huge and innovative step ahead

Material	Alloy #7075-T651
Function	2.4 GHz Wireless control lever up & down
Offset	20 mm.
Dia.	30.9/ 31.6 mm.
Length	426 mm./Travel 120 mm. 466 mm./Travel 140 mm.
Weight	690g/ 30.9*466 mm.
Finish	Polished Black
Shaft finish	Hard Anodized Black



2.4 GHz Wireless Transmission



Alloy 7075



140 mm Travel



Light Weight



Cartridge Replaceable



PSI Pressure Adjustable



Wireless Control



Removable battery

JD - YSP07

NEW

pat. ISO MTB

150mm travel ICR (internal cable routing) version offering wider range for different riders

Material	Alloy #7075-T651
Function	Control lever up & down
Offset	0 mm.
Dia.	30.9/ 31.6 mm.
Length	455 mm./Travel 150 mm.
Weight	550g/30.9*455 mm.
Finish	Polished Black
Shaft finish	Hard Anodized Black



Internal Routing



Alloy 7075



150 mm Travel



Light Weight



Cartridge Replaceable



PSI Pressure Adjustable



DROPPER POST

JD - YSP12

NEW pat.
ISO MTB

Popular ICR (internal cable routing) version offering stealth and clean outlook

- Material** AL7075-T651
- Function** Control lever up & down
- Load setting** 200 kg
- Offset** 0 mm.
- Dia.** 30.9/31.6 mm.
- Length** 330 mm./Travel 80 mm.
370 mm./Travel 100 mm.
410 mm./Travel 120 mm.
420 mm./Travel 125 mm.
- Weight** Weight: 535g/30.9*410 mm.
- Finish** Polished Black
- Shaft finish** Hard Anodized Black



JD - YSP12L



JD - YSP15

NEW pat.
ISO MTB *

Best value ICR (internal cable routing) version offering stealth and clean outlook

- Material** Alloy #6061-T6
- Function** Control lever up & down
- Load setting** 90 kg
- Offset** 0 mm.
- Dia.** 30.9/31.6 mm.
- Length** 315 mm./Travel 80 mm.
360 mm./Travel 100 mm.
400 mm./Travel 120 mm.
- Weight** 600g/30.9*400 mm.
(excluding cable set 90g)
- Finish** Polished Black
- Shaft finish** Hard Anodized Black



* stage 2 standard according to suspension system



JD - YSP11

NEW ISO MTB

27.2 ICR (internal cable routing) version offering stealth and clean outlook 200 kg. load setting

- Material** Alloy #7075-T651
- Function** Control lever up & down
- Offset** 0 mm.
- Dia.** 27.2 mm.
- Length** 300 mm./Travel 65 mm.
350 mm./Travel 85 mm.
400 mm./Travel 105 mm.
- Weight** 530g/27.2*350 mm.
(excluding cable set 90g)
- Finish** Polished Black
- Shaft finish** QPQ



DROPPER POST



JD - YSP02

pat.
ISO MTB *

Unique, elegant and easy to assemble head design

Material	☑ Alloy #6061-T6
Function	☑ Control lever up & down
Load setting	☑ 70kg/90kg
Offset	☑ 15 mm.
Dia.	☑ 30.9/31.6/33.9 mm.
Length	☑ 350 mm./Travel 80 mm. 400 mm./Travel 100 mm. 425 mm./Travel 120 mm.
Weight	☑ 738g/31.6*400 mm.
Finish	☑ Polished Black
Shaft finish	☑ Hard Anodized Black



* stage 2 standard according to suspension system



JD - YSP01

ISO MTB *

AM bike adjustable seat post - Freely, fit the terrain you meet!
The Pinocchio tool less height MICRO adjustable post offers a quick and easy lowering task
• Reliable and solid technology - Virtually No Play!
• Exquisite elegant and easy assembling w/low profile head design

Material	☑ Alloy #6061-T6
Function	☑ Control lever up & down
Load setting	☑ 70kg/90kg
Offset	☑ 15 mm.
Dia.	☑ 30.9/31.6/33.9 mm.
Length	☑ 350 mm./Travel 80 mm. 400 mm./Travel 100 mm. 425 mm./Travel 120 mm.
Weight	☑ 640g/30.9*400 mm.
Finish	☑ Polished Black
Shaft finish	☑ Hard Anodized Black



* stage 2 standard according to suspension system

JD - YSP02 27.2mm

pat.
ISO MTB *

The new convert version of external dropper seat post-27.2mm
Aggressive light weight design w/ Alloy #7075 material
Special air pressure actuation to provide up to 200 kgs weight loading

Material	☑ Alloy #7075-T651
Function	☑ Control lever up & down
Load setting	☑ 200kg
Offset	☑ 15 mm.
Dia.	☑ 27.2 mm.
Length	☑ 280 mm./Travel 60 mm. 330 mm./Travel 80 mm.
Weight	☑ 452g/27.2*280 mm. (excluding cable set 90g)
Finish	☑ Polished Black
Shaft finish	☑ Hard Anodized Black



* stage 2 standard according to suspension system

